
Bushings and Hubs FX keyless bushings

## PHF FX190-140X230



5		D1100
	Bushing no.	FX190
	d (mm)	140
	d (in)	5.51
	D (mm)	230
	d <sub>w</sub> (mm)	95
	L (mm)	60.5
	L <sub>1</sub> (mm)	46
	L <sub>2</sub> (mm)	-
	L₃ (mm)	-
	B (mm)	0
	D <sub>1</sub> (mm)	-
	d <sub>1</sub> (mm)	175
	e (mm)	7.25
	F <sub>t</sub> Transmissible	367
	axial force (kN)	
	M <sub>t</sub> Transmissible	15100
	torque (Nm)	
	P <sub>w</sub> Shaft surface	-
1000	pressure (N/mm²)	
	P <sub>n</sub> Hub surface	-
	pressure (N/mm²)	
	Clamp screws Qty	10
	Clamp screws size	M12
	Clamp screws nut	-
	M <sub>s</sub> Screw	100
	tightening torque	
	(Nm)	
	Weight (kg)	10

® SKF is a registered trademark of the SKF Group
© SKF Group 2012

The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.

