
Bushings and Hubs FX keyless bushings

## PHF FX190-240X405



5		
	Bushing no.	FX190
	d (mm)	240
A	d (in)	9.45
	D (mm)	405
	d <sub>w</sub> (mm)	170
	L (mm)	109
And a state of the	L <sub>1</sub> (mm)	92
A	L <sub>2</sub> (mm)	-
	L <sub>3</sub> (mm)	-
	B (mm)	0
Provide and a second	D <sub>1</sub> (mm)	-
	d <sub>1</sub> (mm)	295
deserves of	e (mm)	8.5
	F <sub>t</sub> Transmissible	1464
	axial force (kN)	
Contraction of the local distance of the loc	M <sub>t</sub> Transmissible	120000
	torque (Nm)	
	P <sub>w</sub> Shaft surface	-
	pressure (N/mm²)	
	P <sub>n</sub> Hub surface	-
	pressure (N/mm²)	
	Clamp screws Qty	12
	Clamp screws size	M20
	Clamp screws nut	-
And and a state of the	M <sub>s</sub> Screw	490
	tightening torque	
	(Nm)	
	Weight (kg)	67

® SKF is a registered trademark of the SKF Group
© SKF Group 2012

The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.

